



# SAFETY DATA SHEET

## SECTION 1. Identification of the hazardous chemical substance or mixture and of the supplier or manufacturer

<b>Name of the hazardous chemical substance or mixture</b>	Dry Moly Lube - 311 g	
<b>Other means of identification</b>		
Product Code	Item# 1750667	
<b>Recommended use of the hazardous chemical substance or mixture, and restrictions of use</b>		
Recommended use	Dry film lubricant	
Recommended restrictions	None known.	
<b>Suppliers details</b>		
Company name	CRC Industrias de Mexico S. de R. L. de C.V.	
Address	Cerrada Canadá 201-H Fraccionamiento Industrial Martel Santa Catarina, NL 66367 Mexico	
Telephone	General Information	81-2139-0572
Website	crc-mexico.com	
E-mail	SoporteTecnico@crcind.com	
<b>Emergency phone number</b>	24-Hour Emergency	800-681-9531

## SECTION 2. Hazard identification

### Classification of the substance or mixture

<b>Physical hazards</b>	Aerosols	Category 1
<b>Health hazards</b>	Skin corrosion/irritation	Category 3
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3

### Elements of labeling, including precautionary statements and warning pictograms



**Signal word** Danger

#### Hazard statement

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H316	Causes mild skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statement

##### Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe mist/vapors.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear eye protection/face protection.

**Response**

P332 + P313 If skin irritation occurs: Get medical attention.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical attention.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal**

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards which do not result in classification**

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**Supplemental information**

8% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 8% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

**SECTION 3. Composition/information on ingredients**

**Mixtures**

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
acetone		67-64-1	50 - 100
propane		74-98-6	15 - 25
butane		106-97-8	10 - 15
isopropyl alcohol		67-63-0	10 - 15
ethylene glycol propyl ether		2807-30-9	1 - 5
molybdenum disulphide		1317-33-5	1 - 5

**Composition comments** Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

**SECTION 4. First-aid measures**

**Description of necessary first-aid measures**

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.  
**Skin contact** Remove contaminated clothing. Wash off with soap and water. Get medical attention if irritation develops and persists.  
**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.  
**Ingestion** In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Do not induce vomiting.

**Most important symptoms/effects, acute and delayed**

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Mild skin irritation. Prolonged exposure may cause chronic effects.

**Indication of immediate medical attention and special treatment needed**

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## SECTION 5. Fire-fighting measures

**Suitable extinguishing media** Dry chemical powder. Water spray. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical** Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

**Special protective actions for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Fire fighting equipment/instructions** In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

**General fire hazards** Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

## SECTION 6. Measures that must be taken in the event of accidental spillage or an accidental leak

### Personal precautionary measures, protective equipment and emergency procedure

**For non-emergency personnel** Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**For emergency responders** Keep unnecessary personnel away. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Ventilate closed spaces before entering them. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

**Methods and materials for containing and cleaning up spills or releases** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

## SECTION 7. Handling and storage

**Precautions for safe handling** Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist/vapors. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

**Conditions for safe storage, including any incompatibilities** Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

## SECTION 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

##### Mexico. Occupational Exposure Limit Values

Components	Type	Value
acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
butane (CAS 106-97-8)	TWA	1000 ppm
	STEL	400 ppm
isopropyl alcohol (CAS 67-63-0)	TWA	200 ppm
	TWA	1000 ppm

##### US. ACGIH Threshold Limit Values

Components	Type	Value
acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
butane (CAS 106-97-8)	STEL	1000 ppm
	STEL	400 ppm
	TWA	200 ppm

#### Biological limit values

##### Mexico. Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	50 mg/l	Acetona	Urine	*
isopropyl alcohol (CAS 67-63-0)	40 mg/l	Acetona	Urine	*

\* - For sampling details, please see the source document.

##### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
isopropyl alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

#### Control banding approach

Not available.

#### Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Hazardous Chemicals (NOM-028-STPS-2012, System for administration of workplace safety in the process and critical equipment for handling hazardous chemicals, Appendix A, Table A.I, 9/6/2012)

butane (CAS 106-97-8)	4600 KG
isopropyl alcohol (CAS 67-63-0)	4600 KG
propane (CAS 74-98-6)	4600 KG

#### Individual protection measures, such as personal protective equipment (PPE)

**Eye/face protection** Use eye protection conforming to EN 166.

#### Skin protection

**Hand protection** When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Suitable gloves can be recommended by the glove supplier. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.

**Other** Wear appropriate chemical resistant clothing.

<b>Respiratory protection</b>	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

## SECTION 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol.
<b>Color</b>	Black.
<b>Odor</b>	Aromatic.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-138.5 °F (-94.7 °C) estimated
<b>Initial boiling point and boiling range</b>	132.9 °F (56.1 °C) estimated
<b>Flash point</b>	-4.0 °F (-20.0 °C)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	1.7 %
<b>Explosive limit - upper (%)</b>	12 %
<b>Vapor pressure</b>	233 hPa
<b>Vapor pressure temp.</b>	68 °F (20 °C)
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.8
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	410 °F (210 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Molecular weight</b>	Not available.
<b>Other information</b>	
<b>Percent volatile</b>	97 %

---

## SECTION 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions that must be avoided</b>	Avoid overheating or freezing. Heat, flames and sparks.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides. Sulfur oxides. Metal oxides.

## SECTION 11. Toxicological information

### Information about likely routes of entry

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes mild skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Based on available data, the classification criteria are not met.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Mild skin irritation.
---	--

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Numerical measures of toxicity (such as acute toxicity estimates)

**Acute toxicity** Based on available data, the classification criteria are not met.

Components	Species	Test Results
ethylene glycol propyl ether (CAS 2807-30-9)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	0.87 g/kg
<b>Oral</b>		
LD50	Rat	4.45 g/kg

**Skin corrosion/irritation** Causes mild skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

#### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

#### ACGIH Carcinogens

acetone (CAS 67-64-1)	A4 Not classifiable as a human carcinogen.
isopropyl alcohol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.
molybdenum disulphide (CAS 1317-33-5)	A3 Confirmed animal carcinogen with unknown relevance to humans.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Other information** Prolonged inhalation may be harmful.

## SECTION 12. Ecotoxicological information

**Toxicity** Harmful to aquatic life with long lasting effects.

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

#### Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

acetone	-0.24
butane	2.89
isopropyl alcohol	0.05
propane	2.36

**Mobility in soil** No data available.

**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

## SECTION 13. Disposal considerations

### Disposal methods

**Disposal instructions** Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## SECTION 14. Transport information

### SCT

**UN number** UN1950  
**Proper shipping name** AEROSOLS, Limited Quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards** No.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

### DOT

**UN number** UN1950  
**Proper shipping name** Aerosols, flammable, Limited Quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** No.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Special provisions** N82  
**Packaging exceptions** 306  
**Packaging non bulk** None  
**Packaging bulk** None

### IATA

**UN number** UN1950  
**Proper shipping name** Aerosols, flammable, Limited Quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**ERG Code** 10L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**  
**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.

### IMDG

**UN number** UN1950  
**Proper shipping name** AEROSOLS, Limited Quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.

**Environmental hazards**

**Marine pollutant**

No.

**EmS**

F-D, S-U


**Special precautions for user**

Read safety instructions, SDS and emergency procedures before handling.


**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

**DOT; IMDG; SCT**



**IATA**



**SECTION 15. Regulatory information**

**Safety, health and environmental regulations specific for the hazard chemical substance or mixture in question**

This safety data sheet was prepared in accordance with the Official Mexican Standard (NOM-018-STPS-2015).

**Mexico. Substances subject to reporting for the pollutant release and transfer registry (PRTR)**

Not listed.

**International regulations**

**Montreal Protocol**

Not applicable.

**Stockholm Convention**

Not applicable.

**Rotterdam Convention**

Not applicable.

**Kyoto protocol**

Not applicable.

**Basel Convention**

Not applicable.

**International Inventories**

**Country(s) or region**

**Inventory name**

**On inventory (yes/no)\***

Australia

Australian Inventory of Industrial Chemicals (AICIS)

Yes

Canada

Domestic Substances List (DSL)

Yes

Canada

Non-Domestic Substances List (NDSL)

No

China

Inventory of Existing Chemical Substances in China (IECSC)

Yes

Europe

European Inventory of Existing Commercial Chemical Substances (EINECS)

Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## SECTION 16. Other included information relevant to the preparation and updating of safety data sheets

Issue date	12-04-2019
Revision date	04-05-2023
Version #	02

### List of abbreviations

ACGIH: American Conference of Governmental Industrial Hygienists.  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.  
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.  
ANTT: National Agency of Land Transport.  
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).  
CAS: Chemical Abstract Service.  
Ceiling: Short Term Exposure Limit Ceiling value.  
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.  
DOT: Department of Transportation.  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
GWP: Global Warming Potential.  
IARC: International Agency for Research on Cancer.  
IATA: International Air Transport Association.  
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.  
IMDG: International Maritime Dangerous Goods.  
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).  
MARPOL: International Convention for the Prevention of Pollution from Ships.  
NFPA: National Fire Protection Association.  
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).  
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.  
SCT: Secretariat of Communications and Transportation (NOM-002-SCT/2011).  
STEL: Short term exposure limit.  
TLV: Threshold Limit Value.  
TWA: Time Weighted Average.  
VOC: Volatile organic compounds.  
STEL: Short-term Exposure Limit.

**References**

NMX-R-019-SCFI-2011 - Harmonized system of classification and communication of dangers of chemical products  
NOM-010-STPS-2014 (second revision) – Occupational Exposure Limits – becomes effective on April 28, 2016  
NOM-018-STPS-2015 - Harmonized system for the identification and communication of hazards and risks for hazardous chemicals in the workplace  
NOM-026-STPS-2008 - Colors and signals of safety and hygiene, and risk identification through fluids in pipes  
NOM-028-STPS-2012 – Work-Safety Management System for Processes and Critical Equipment Handling Hazardous Chemical Substances  
NOM-047-SSA1-2011 – Workplace Biological Exposure Indices (BEIs) to Chemical Substances  
Workplace Threshold Quantities of Hazardous Chemicals

**Disclaimer**

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industrias de Mexico S. de R. L. de C.V..

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.