



SAFETY DATA SHEET

SECTION 1. Identification of the hazardous chemical substance or mixture and of the supplier or manufacturer

Name of the hazardous chemical substance or mixture Power Lube High Performance Lubricant w/PTFE - 311 g

Other means of identification

Product Code Item# 1751408

Recommended use of the hazardous chemical substance or mixture, and restrictions of use

Recommended use Multi-purpose lubricant

Recommended restrictions None known.

Suppliers details

Company name CRC Industrias de Mexico S. de R. L. de C.V.
Address Cerrada Canadá 201-H

Fraccionamiento Industrial Martel
Santa Catarina, NL 66367
Mexico

Telephone General Information 81-2139-0572

Website www.crc-mexico.com

E-mail SoporteTecnico@crcind.com

Emergency phone number 24-Hour Emergency 01-800-681-9531

SECTION 2. Hazard identification

Classification of the substance or mixture

Physical hazards Aerosols Category 1

Health hazards Acute toxicity, dermal Category 5

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2

Elements of labeling, including precautionary statements and warning pictograms



Signal word Danger

Hazard statement

H222 Extremely flammable aerosol.
H229 Pressurized container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H313 May be harmful in contact with skin.
H401 Toxic to aquatic life.

Precautionary statement

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P312 Call a POISON CENTER/doctor if you feel unwell.

Storage

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

None known.

Supplemental information

When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride.

SECTION 3. Composition/information on ingredients

Mixtures

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
distillates (petroleum), hydrotreated light		64742-47-8	50 - 60
paraffin oils (petroleum), catalytic dewaxed heavy		64742-70-7	5 - 10
paraffin oils (petroleum), catalytic dewaxed light		64742-71-8	5 - 10
butyl stearate		123-95-5	3 - 5
methyl acetate		79-20-9	3 - 5
antimony tris[o,o-dipropyl] tris(dithiophosphate)		15874-48-3	1 - 3
carbon dioxide		124-38-9	1 - 3
methyl salicylate		119-36-8	1 - 3
petrolatum		8009-03-8	1 - 3
sorbitan monooleate		1338-43-8	1 - 3

Composition comments Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4. First-aid measures

Description of necessary first-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact Wash off with soap and water. Get medical advice/attention if you feel unwell. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
Eye contact Rinse with water. Get medical attention if irritation develops and persists.
Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. Fire-fighting measures

Suitable extinguishing media Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective actions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Will burn if involved in a fire.

SECTION 6. Measures that must be taken in the event of accidental spillage or an accidental leak

Personal precautionary measures, protective equipment and emergency procedure

For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containing and cleaning up spills or releases Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

SECTION 7. Handling and storage

Precautions for safe handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 2 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Mexico. Occupational Exposure Limit Values

Components	Type	Value
antimony tris[o,o-dipropyl] tris(dithiophosphate) (CAS 15874-48-3)	TWA	0.5 mg/m ³
butyl stearate (CAS 123-95-5)	TWA	10 mg/m ³
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm

Mexico. Occupational Exposure Limit Values

Components	Type	Value
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m3
methyl acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	TWA	5 mg/m3
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	TWA	5 mg/m3
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
antimony tris[o,o-dipropyl] tris(dithiophosphate) (CAS 15874-48-3)	TWA	0.5 mg/m3	
butyl stearate (CAS 123-95-5)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
methyl acetate (CAS 79-20-9)	STEL	250 ppm	
	TWA	200 ppm	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	TWA	5 mg/m3	Inhalable fraction.
petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Mexico OELs: Skin designation

distillates (petroleum), hydrotreated light (CAS 64742-47-8) Can be absorbed through the skin.

Control banding approach Not available.

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Hazardous Chemicals (NOM-028-STPS-2012, System for administration of workplace safety in the process and critical equipment for handling hazardous chemicals, Appendix A, Table A.I, 9/6/2012)

distillates (petroleum), hydrotreated light (CAS 64742-47-8) 4600 KG

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Neoprene. Nitrile.

Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Amber.
Odor	Wintergreen.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-144.4 °F (-98 °C) estimated
Initial boiling point and boiling range	134.2 °F (56.8 °C) estimated
Flash point	< 20 °F (< -6.7 °C)
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	16 % estimated
Vapor pressure	1616.1 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.86 estimated
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	428 °F (220 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Molecular weight	Not available.
Other information	
Percent volatile	86.9 % estimated

SECTION 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions that must be avoided	Heat, flames and sparks. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Hydrogen fluoride. Metal oxides. Phosphorous oxides. Sulfur oxides.

SECTION 11. Toxicological information

Information about likely routes of entry

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May be harmful in contact with skin.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea.

Delayed and immediate effects and also chronic effects from short and long term exposure

Numerical measures of toxicity (such as acute toxicity estimates)

Acute toxicity May be fatal if swallowed and enters airways. May be harmful in contact with skin.

Components	Species	Test Results
antimony tris[o,o-dipropyl] tris(dithiophosphate) (CAS 15874-48-3)		
Acute		
Dermal		
LD50	Rabbit	3936 mg/kg
Oral		
LD50	Rat	4965 mg/kg
butyl stearate (CAS 123-95-5)		
Acute		
Oral		
LD50	Rat	32 g/kg
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg, 2.5 hours
methyl acetate (CAS 79-20-9)		
Acute		
Oral		
LD50	Rabbit	3.7 g/kg
methyl salicylate (CAS 119-36-8)		
Acute		
Oral		
LD50	Rat	0.887 g/kg
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
petrolatum (CAS 8009-03-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
sorbitan monooleate (CAS 1338-43-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 20 mg/l, 4 hours
Oral		
LD50	Rat	39800 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
ACGIH Carcinogens		
butyl stearate (CAS 123-95-5)	A4 Not classifiable as a human carcinogen.	
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	A4 Not classifiable as a human carcinogen.	
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	A4 Not classifiable as a human carcinogen.	
petrolatum (CAS 8009-03-8)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Other information	Not available.	

SECTION 12. Ecotoxicological information

Components	Species	Test Results
Toxicity Toxic to aquatic life.		
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
		> 1000 mg/l, 48 hours
		> 1000 mg/l, 96 hours

Components	Species	Test Results
methyl acetate (CAS 79-20-9)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 295 - 348 mg/l, 96 hours
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia > 100 mg/l, 48 hours
sorbitan monooleate (CAS 1338-43-8)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) > 1000 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

methyl acetate	0.18
methyl salicylate	2.55

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13. Disposal considerations

Disposal methods

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. Transport information

SCT

UN number	UN1950
Proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Bulk special provisions	63,190,277,327,344

DOT

UN number	UN1950
Proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306

Packaging non bulk None
Packaging bulk None

IATA


UN number UN1950
Proper shipping name Aerosols, flammable, Limited Quantity
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group Not applicable.
ERG Code 10L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG


UN number UN1950
Proper shipping name AEROSOLS, Limited Quantity
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group Not applicable.
Environmental hazards
Marine pollutant No.
EmS Not available.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT; IMDG; SCT



IATA



SECTION 15. Regulatory information

Safety, health and environmental regulations specific for the hazard chemical substance or mixture in question

Mexico. Hazard identification guidance list (NOM-018-STPS)

antimony tris[o,o-dipropyl] tris(dithiophosphate) (CAS 15874-48-3)	Listed.
butyl stearate (CAS 123-95-5)	Listed.
carbon dioxide (CAS 124-38-9)	Listed.

distillates (petroleum), hydrotreated light (CAS 64742-47-8)	Listed.
methyl acetate (CAS 79-20-9)	Listed.
methyl salicylate (CAS 119-36-8)	Listed.
paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)	Listed.
paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)	Listed.
petrolatum (CAS 8009-03-8)	Listed.

Mexico. Substances subject to reporting for the pollutant release and transfer registry (PRTR)

carbon dioxide (CAS 124-38-9)	100000 KG
-------------------------------	-----------

International regulations

Montreal Protocol

Not applicable.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

carbon dioxide (CAS 124-38-9)	Listed.
-------------------------------	---------

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16. Other included information relevant to the preparation and updating of safety data sheets

Issue date	04-12-2019
Revision date	11-21-2019
Version #	02

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
DOT: Department of Transportation (49 CFR 172.101).
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

	<p>IMDG Code: International Maritime Dangerous Goods Code. MARPOL: International Convention for the Prevention of Pollution from Ships. SCT: Secretariat of Communications and Transportation (NOM-002-SCT/2011).</p>
References	<p>Workplace Threshold Quantities of Hazardous Chemicals NOM-047-SSA1-2011 – Workplace Biological Exposure Indices (BEIs) to Chemical Substances NOM-028-STPS-2012 – Work-Safety Management System for Processes and Critical Equipment Handling Hazardous Chemical Substances NOM-018-STPS-2000 – Workplace Hazardous Chemical Substances Communication and Identification Standard NOM-010-STPS-2014 (second revision) – Occupational Exposure Limits – becomes effective on April 28, 2016</p>
Further information	<p>CRC # 1751766</p>
Disclaimer	<p>This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.</p> <p>The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industrias de Mexico S. de R. L. de C.V..</p>
Revision information	<p>This document has undergone significant changes and should be reviewed in its entirety.</p>